



**R32**  
Refrigerant



**INVERTER**

			1HP	1.5HP	2HP	2.5HP	3HP	
容量 Capacity	額定製冷量 Cooling rated	kW	2.5	3.5	5.0	6.0	7.1	
		Btu/h	8,500	11,900	17,100	20,500	24,200	
	最低 - 最高 Min - Max		3,400 - 11,600	4,100 - 13,000	5,500 - 20,500	5,500 - 22,900	7,200 - 25,600	
	額定供暖量 Heating rated	kW	2.5	3.5	5.0	6.0	7.1	
		Btu/h	8,500	11,900	17,100	20,500	24,200	
	最低 - 最高 Min - Max		3,400 - 11,600	4,100 - 13,000	5,500 - 20,500	5,500 - 22,900	7,200 - 25,600	
電源 Power supply			單相 1 phase, 220-240 V, 50 Hz					
運行電流 Running current	製冷 Cooling	額定 Rated	A	2.9	4.6	6.1	8.0	10.9
	供暖 Heating			3.0	4.6	6.1	8.3	10.9
耗電量 Power consumption	製冷 Cooling	額定 Rated	W	610	980	1,315	1,740	2,370
	供暖 Heating			610	980	1,315	1,740	2,370
製冷季節性表現係數 (CSPF)			5.74	5.03	5.95	5.38	5.17	
製熱季節性表現係數 (HSPF)			5.07	4.91	4.18	4.72	4.35	
<b>室內機 INDOOR UNIT</b>			<b>FTHM25RAV1N</b>	<b>FTHM35RAV1N</b>	<b>FTHM50RAV1N</b>	<b>FTHM60RAV1N</b>	<b>FTHM71RAV1N</b>	
面板顏色 Front panel colour			亮白色 Shiny white					
排風量 (高) Airflow rate (H)	製冷 Cooling	m <sup>3</sup> /min (cfm)	10.2 (360)	10.7 (378)	18.2 (643)	18.2 (643)	20.1 (710)	
	供暖 Heating		10.3 (364)	10.8 (381)	19.5 (689)	19.5 (689)	21.5 (759)	
風速 Fan speed			五段風速、寧靜和自動 5 steps, quiet & automatic					
運轉音量 (高/中/低/超低) Sound levels (H/M/L/SL)	製冷 Cooling	dB(A)	40 / 35 / 29 / 25	41 / 36 / 30 / 26	44 / 40 / 35 / 28	44 / 41 / 36 / 30	46 / 42 / 37 / 31	
	供暖 Heating		40 / 35 / 30 / 27	41 / 36 / 31 / 28	44 / 40 / 35 / 32	45 / 40 / 35 / 32	46 / 42 / 37 / 34	
尺寸 Dimensions		高x闊x深 HxWxD	mm 283 x 770 x 226			295 x 990 x 266		
重量 Weight		kg	8			13		

# 室外機 OUTDOOR UNIT

RHM25RAV1N

RHM35RAV1N

RHM50RAV1N

RHM60RAV1N

RHM71RAV1N

機殼顏色 Casing colour

象牙白色 Ivory white

壓縮機 Compressor

類型 Type

密封擺動式 Hermetically sealed swing type

馬達輸出 Motor output

W

700

700

1,200

1,300

製冷劑 Refrigerant

類型 Type

R32

製冷劑量 Charge

kg

0.70

0.70

1.00

1.05

運轉音量 (高/超低)  
Sound levels (H / SL)

製冷 Cooling

dB(A)

48 / 44

48 / 45

47 / 44

47 / 44

51 / 45

供暖 Heating

dB(A)

48 / 44

48 / 45

48 / 45

49 / 45

52 / 46

尺寸 Dimension

高x闊x深 HxWxD

mm

550 x 658 x 275

595 x 845 x 300

重量 Weight

kg

27

36

39

運轉範圍 Operation range

製冷 Cooling

°CDB

10.0 to 46.0

供暖 Heating

°CDB

2.0 to 20.0

配管直徑 Piping connection

液態 Liquid

mm

ø6.4

氣態 Gas

mm

ø9.5

ø12.7

ø15.9

排水 Drain

mm

ø16.0

最長喉管長度 Max. piping length

m

15

30

最大高低差 Max. level difference

12

20